

ODYSSEY[®] BATTERY

The battery you can depend on for your fleet

Extreme power, performance and durability

With today's no idling laws, fleet owners and managers must face the harsh reality that drivers must shut off their engines and rely on the batteries to power critical auxiliary and hotel loads. These frequent deep discharges shorten the life of conventional Starting, Lighting and Ignition (SLI) batteries. This results in costly battery replacements as well as the potential for increased downtime and costs for jump starts.

The answer – the revolutionary ODYSSEY[®] Performance and ODYSSEY Extreme batteries. Thanks to their unique Thin Plate Pure Lead (TPPL) technology design and massive deep cycling capability, these virtually maintenance-free, Absorbed Glass Mat (AGM) design batteries have the reserve power to run on-board accessories with the engine off – without shortening battery life.



ODYSSEY[®] CONNECT

BATTERY MONITORING SYSTEM

Check battery* health issues,
long before issues arise.



Scan to learn more

*ODYSSEY Connect battery monitoring system is available with Connect enabled ODYSSEY batteries, including ODX-ACE31.

MILITARY GRADE PLATE DESIGN

Made from 99% pure lead and built to stand up to the harshest environments. ODYSSEY batteries offer slower self-discharge, less corrosion and faster recharging.

VIBRATION RESISTANCE

Protection against high impact shock and vibration that cause premature battery failure.

EXTREME TEMPERATURE TOLERANCE

Operating temperatures:
-40°F (-40°C) to 140°F (60°C) – Performance batteries
-40°F (-40°C) to 176°F (80°C) – Extreme batteries

LONGER SERVICE LIFE

Three times longer than conventional batteries.

ODYSSEY® Extreme Batteries

12 volt

PART NUMBER	PHCA 5 sec [A]	CCA [A]	Ah at 20-hr rate	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [lb (kg)]
ODX-AGM31	2150	1150	103	220	13.0 (330)	6.8 (173)	9.5 (241)	8.5 (216)	78 (35.5)

Construction	Thin Plate Pure Lead (TPPL) Absorbed Glass Mat (AGM)
Case Material	Polycarbonate Blend*
Terminals	Stainless steel stud with lead base
Top Lead Style	Over-the-wall**
Warranty	Limited 4-year replacement period; 2-year in APU applications



ODX-AGM31

ODYSSEY® Extreme Batteries with ODYSSEY Connect System

12 volt

PART NUMBER	PHCA 5 sec [A]	CCA [A]	Ah at 20-hr rate	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [lb (kg)]
ODX-ACE31	2150	1150	103	220	13.0 (330)	6.8 (173)	9.5 (241)	8.5 (216)	78 (35.5)

Construction	Thin Plate Pure Lead (TPPL) Absorbed Glass Mat (AGM)
Case Material	Polycarbonate Blend*
Terminals	Stainless steel stud with lead base
Top Lead Style	Over-the-wall**
Warranty	Limited 4-year replacement period; 2-year in APU applications



ODX-ACE31

ODYSSEY® Performance Batteries

12 volt

PART NUMBER	PHCA 5 sec [A]	CCA [A]	Ah at 20-hr rate	Reserve Capacity [Minutes]	Maximum Length [in (mm)]	Maximum Width [in (mm)]	Maximum Total Height [in (mm)]	Maximum Container Height [in (mm)]	Weight [lb (kg)]
ODP-AGM31	1750	925	103	200	13.0 (330)	6.8 (173)	9.6 (243)	8.6 (219)	70 (31.5)

Construction	Thin Plate Pure Lead (TPPL) Absorbed Glass Mat (AGM)
Case Material	Polypropylene
Terminals	Stainless steel stud with lead base
Top Lead Style	Through-the-wall
Warranty	Limited 3-year replacement period; 2-year in APU applications



ODP-AGM31

*Polycarbonate Blend - Stronger for more rugged environments

**Over-the-wall - Offers lower resistance for higher capacity, as compared to through-the-wall type



EnerSys World Headquarters
2366 Bernville Road
Reading, PA 19605, USA
Tel: +1-800-964-2837

EnerSys EMEA
EH Europe GmbH
Baarerstrasse 18
6300 Zug, Switzerland

EnerSys Asia
152 Beach Road
#11-08 Gateway East Building
Singapore 189721
Tel: +65 6431 3700

Want more info?
Scan code to access
the ODYSSEY® Battery
Literature Library

